



Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\W

LENGTH OF PROJECT BEARDSLEY ROAD	NUMPER
BEGINNING OF PROJECT STA. 21+70, C.L. END OF PROJECT STA. 28+00, C.L.	PE-200000103
PROJECT LENGTH APPROX. 630 FT.	DATE
	DATE PREPARED
	ROUTE STATE BEARDSLEY
	DISTRICT SHEET NO.
	JACKSON KCMO PROJECT NO.
	89005585 BRIDGE NO. S030B42
APPROVED BY:	
	NOIL
CHAD THOMPSON, ASST. CITY ENGINEER	SCRIP
DATE	DE
	DATE
CITT ENGINEER	S SE OUR I
DATE	RDAL PAIRS DAMA(DAMA(MISS
	SLEY E REI IRE I ANDSL ITY.
	EARD RIDG A L/ AS CI
SHERRI MCINTYRE, DIRECTOR OF PUBLIC WORKS	B B 20 KANS,
DATE	
DATE	0024
	L F0097
CERTIFICATION HEREBY CERTIFY THAT THIS PROJECT HAS BEEN IGNED, AND THESE PLANS PREPARED, TO MEET EXCEED THE DESIGN CRITERIA OF KANSAS CITY, SOURI, IN CURRENT USAGE EXCEPT AS INDICATED OW. EPTIONS:	CONTRESSIVE SULTE 220 MO 64105 FAX 913/441-1468 F AUTHORITY NUMBEF
	d Str 1TY. ATE 0
	SAS C 221-C
	14 V KANS 816, CER1
ROBERT KREWSON, P.E.	DRAWN BY: JSB
	CHECKED BY: JMR

GENERAL NOTES DESIGN SPECIFICATION: 2002 EDITION OF THE AASHTO STANDARD SPECIFICATIONS FOR HIGHWAY BRIDGES (FROM ORIGINAL DESIGN). CONSTRUCTION SPECIFICATIONS: 2018 MISSOURI STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION WITH PROJECT SPECIAL PROVISIONS (IF INCLUDED IN THE PROJECT MANUAL). STANDARD SPECIFICATIONS AND DESIGN CRITERIA, CITY OF KANSAS CITY, MISSOURI. INSPECTION REPORT: REFER TO THE "SPECIAL INSPECTION MEMO (BEARDSLEY BRIDGE SO3OB42)" DATED 8/30/2018. (AVAILABLE UPON REQUEST FROM THE CITY'S PUBLIC WORKS DEPARTMENT). THE INSPECTION REPORT WILL BE REFERRED TO THROUGHOUT THESE NOTES FOR SPECIFIC ITEMS OF WORK. EXISTING BRIDGE PLANS: SPECIFIC SHEETS OF THE EXISTING PLANS ARE INCLUDED IN THIS PLAN FOR REFERENCE ONLY. A FULL SET OF EXISTING BRIDGE PLANS IS AVAILABLE UPON REQUEST FROM THE CITY'S PUBLIC WORKS DEPARTMENT. EXISTING DIMENSION VERIFICATION: DIMENSIONS OF THE EXISTING STRUCTURE ARE BASED ON EXISTING PLANS. VERIFY, BY FIELD MEASUREMENT, THE AS-BUILT DIMENSIONS OF THE EXISTING STRUCTURE AND SUBMIT SUCH VERIFICATION IN WRITING TO THE ENGINEER. THE VERIFICATION WILL INCLUDE SKETCHES, DRAWINGS, PHOTOGRAPHS AND DESCRIPTIONS AS NEEDED TO CLEARLY DEFINE THE AS-BUILT DIMENSIONS THAT WILL BE INCORPORATED IN THE NEW CONSTRUCTION. SEQUENCE OF CONSTRUCTION: THE GENERAL SEQUENCE OF CONSTRUCTION SHALL BE AS FOLLOWS: 1. HEAT STRAIGHTEN THE STRUCTURAL STEEL 2. BENT PLATE DIAPHRAGM REPLACEMENT 3. INSTALL INTERMEDIATE STIFFENERS 4. CONCRETE REPAIR OF CAP AT BENT 2 5. BEARING DEVICE REPLACEMENT 6. INSTALL ROCK BLANKET 7. SLOPE STABILITY REPAIR 8. STREET LIGHT REPAIR 9. LED LUMINAIRE REPLACEMENT 10. BARRIER CURB REPAIR 11. CLEAN EXPANSION JOINTS 12. DECK OVERLAY 13. OTHER REPAIRS NOT LISTED ABOVE ANY DEVIATION TO THE SEQUENCE OF CONSTRUCTION MUST BE APPROVED BY THE ENGINEER. TRAFFIC CONTROL: SEE SHEET NOS. 10 & 11 FOR TRAFFIC CONTROL PLANS. A TRAFFIC BARRIER HAS BEEN INSTALLED ACROSS THE ROADWAY AT BOTH APPROACHES WITH GUARDRAIL POSTS INSTALLED IN THE PAVEMENT, REMOVE THE BARRIERS AND REPAIR THE PAVEMENT ACCORDING TO KCMO STANDARD PLANS SR-1, INCLUDED IN THIS PLAN SET. PAYMENT FOR BARRIER REMOVAL WILL BE COMPLETELY COVERED BY THE CONTRACT LUMP SUM PRICE FOR "TRAFFIC BARRIER REMOVAL". BARRIER MATERIALS WILL BE THE PROPERTY OF THE CITY AFTER REMOVAL. PAYMENT FOR REPAIRS TO THE PAVEMENT WILL BE CONSIDERED COMPLETELY COVERED BY THE CONTRACT UNIT PRICE FOR "STREET CUT RESTORATION. HEAT STRAIGHTENING OF STRUCTURAL STEEL: HEAT STRAIGHTEN THE GIRDERS IN SPAN 2 OF THE BRIDGE. THE LIMITS OF THE WORK ARE DESCRIBED IN THE INSPECTION REPORT. THE CONTRACTOR SHALL SUBMIT THE SELECTED HEAT STRAIGHTENING CONTRACTOR AND PROPOSED METHOD OF HEAT STRAIGHTENING THE GIRDERS TO THE ENGINEER FOR APPROVAL AT LEAST 4 WEEKS PRIOR TO BEGINNING THE WORK. PERFORM THE HEAT STRAIGHTENING PROCEDURE COMPLYING WITH AASHTO/AWS D1.5 (EDITION REFERENCED IN SUBSECTION 705.2E.) "BRIDGE WELDING CODE" AND THE LATEST VERSIONS OF AASHTO'S "STANDARD SPECIFICATIONS FOR HIGHWAY BRIDGES"; AASHTO'S "LRFD BRIDGE CONSTRUCTION SPECIFICATIONS" AND THE FHWA REPORT, "HEAT-STRAIGHTENING REPAIRS OF DAMAGED STEEL BRIDGES". FOLLOWING THE STRAIGHTENING OF A BEND OR BUCKLE, THE SURFACE OF THE METAL WILL BE INSPECTED BY THE ENGINEER FOR EVIDENCE OF FRACTURE, USING THE DYE PENETRANT OR MAGNETIC PARTICLE INSPECTION METHOD. CONCRETE PATCHING: PATCH SPALL ON THE SOUTH FACE AND TOP OF BENT 2 (APPROX. 353 SQ. FT.). PAYMENT WILL BE MADE AS "SUBSTRUCTURE REPAIR (FORMED)". BEARING DEVICE REPLACEMENT: THE BEARING DEVICES AT BENT 2 WILL BE REPLACED. THE CONTRACTOR SHALL SUBMIT HIS PROPOSED METHOD OF REPLACEMENT TO THE ENGINEER FOR APPROVAL 4 WEEKS PRIOR TO BEGINNING WORK. THE STEEL ROLLED BEAMS SHALL BE JACKED SIMULTANEOUSLY A DISTANCE NOT MORE THAN 1 INCH GREATER THAN THE HEIGHT OF THE EXISTING BEARING DEVICE AS DETAILED IN THE EXISTING PLANS. SUBMIT BEARING DEVICE SHOP DRAWINGS TO THE ENGINEER FOR APPROVAL 4 WEEKS PRIOR TO BEGINNING FABRICATION. BEARING DEVICE REPLACEMENT AND THE TEMPORARY SHORING SYSTEM SHALL BE PAID FOR AS "TYPE N PTFE" BEARINGS". THE TEMPORARY SUPPORTS MUST BE CAPABLE OF SAFELY SUPPORTING A SERVICE LOAD OF APPROXIMATELY 50 TONS PER BEAM (FACTOR OF SAFETY NOT INCLUDED). DIAPHRAGM REPLACEMENT: ONE AT A TIME, REPLACE THE BENT PLATE DIAPHRAGMS AT BENT 2 & INTERMEDIATE DIAPHRAGMS IN BAYS 1 & 2 BETWEEN BENTS 2 & 3. SEE SHEET NO. 8 FOR DETAILS. ROCK BLANKET: INSTALL 1 TON ROCK BLANKET BELOW ENTIRE STRUCTURE (APPROX, 2750 SQ, YD,) PAYMENT WILL BE MADE AS "FURNISHING 1 TON ROCK BLANKET" AND "PLACING 1 TON ROCK BLANKET". Detailed FEB 2019

Checked FEB 2019





Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_files\Jbrashears\002_Gen_Plan_and_Notes.dgn 3:49:53_PM_

<u>GENERAL NOTES (cont.)</u>
RESIN ANCHORS: THE CONTRACTOR SHALL USE ONE OF THE QUALIFIED RESIN ANCHOR SYSTEMS IN ACCORDANCE WITH SEC. 1039 OF THE MODOT SPECIFICATIONS.
COST OF FURNISHING AND INSTALLING THE RESIN ANCHOR SYSTEMS, COMPLETE IN PLACE, WILL BE COMPLETELY COVERED BY THE CONTRACT UNIT PRICE FOR "SUBSTRUCTURE REPAIR (FORMED)", SQ. FT., OR "SAFETY BARRIER CURB", LINEAR FOOT.
THE MINIMUM EMBEDMENT DEPTH IN CONCRETE WITH F'C = 4,000 PSI FOR THE RESIN ANCHOR SYSTEMS SHALL BE THAT REQUIRED IN ACCORDANCE WITH SEC 1039 OF THE MODOT SPECIFICATIONS BUT SHALL NOT BE LESS THAN 5".
SAFETY BARRIER CURB REPAIR/REPLACEMENT: THE CONCRETE FOR THE BARRIER CURB REPLACEMENT SHALL BE CLASS B-1. THE MATERIAL USED FOR THE BARRIER CURB REPAIR SHALL BE MCIB "SPECIAL AGGREGATE CONCRETE SA-2" OR AN APPROVED SHOTCRETE.
PAYMENT FOR BARRIER CURB REMOVAL AND ALL CONCRETE AND REINFORCEMENT FOR SAFETY BARRIER CURB, COMPLETE-IN-PLACE, WILL BE CONSIDERED COMPLETELY COVERED BY THE CONTRACT PRICE FOR "SAFETY BARRIER CURB", LINEAR FOOT.
MISCELLANEOUS: Outline of old work is indicated by light dashed lines. Heavy Lines indicate new work.
CONTRACTOR SHALL VERIFY ALL DIMENSIONS IN FIELD BEFORE ORDERING NEW MATERIAL.
BARS BONDED IN OLD CONCRETE NOT REMOVED SHALL BE CLEANLY STRIPPED AND EMBEDDED INTO NEW CONCRETE WHERE POSSIBLE. IF LENGTH IS AVAILABLE, OLD BARS SHALL EXTEND INTO NEW CONCRETE AT LEAST 40 DIAMETERS FOR PLAIN BARS AND 30 DIAMETERS FOR DEFORMED BARS, UNLESS OTHERWISE NOTED.
ALTERNATE 1: REPLACE EXISTING CHAIN LINK FENCE ON WEST SIDEWALK WITH (112 IN.) CURVED PEDESTRIAN CHAIN LINK FENCE, FULL LENGTH OF BRIDGE. INSTALL (112 IN.) CURVED CHAIN LINK FENCE TO EAST BARRIER, FULL LENGTH OF BRIDGE. PAYMENT WILL BE MADE AS "PEDESTRIAN FENCE (STRUCTURES)", LINEAR FOOT.
ALTERNATE 2: SECURITY FENCE: INSTALL SECURITY FENCE (BETAFENCE GUARDIAN 5000 OR EQUAL) UNDERNEATH BRIDGE ON BOTH EAST AND WEST SIDES, FULL LENGTH, PROVIDE THREE (3) ACCESS GATES IN FENCE ON WEST SIDE ONLY, PAYMENT WILL BE MADE AS "SECURITY FENCE", LUMP SUM,
ALTERNATE 3: SECURITY FENCE/CORRUGATED METAL FENCE: INSTALL SECURITY FENCE (BETAFENCE GUARDIAN 5000 OR EQUAL) UNDERNEATH BRIDGE ON WEST SIDE, FULL LENGTH. PROVIDE THREE (3) ACCESS GATES IN FENCE ON WEST SIDE ONLY. PAYMENT WILL BE MADE AS "SECURITY FENCE", LUMP SUM. INSTALL CORRUGATED METAL SHEET PILING AS FENCE UNDERNEATH BRIDGE ON EAST SIDE, FULL LENGTH. CONTRACTOR TO DETERMINE FIXITY AND DRAINAGE AT BASE OF FENCE. PAYMENT WILL BE MADE AS "GALVANIZED CORRUGATED METAL SHEET PILING", SQUARE FOOT.

	BRIDGE QUANTITIES		
	ITEM	UNITS	QUANTITY
	MOBILIZATION	LUMP SUM	1
	EPOXY POLYMER CONCRETE OVERLAY	SQ. YD.	2,422
	SUBSTRUCTURE REPAIR (FORMED)	SQ. FT.	353
	REINFORCING STEEL (BRIDGES)	LBS.	50
*	FABRICATED STRUCTURAL LOW ALLOY STEEL (MISC.) A709 grade 50W	LBS.	1,980
	TYPE N PTFE BEARING	EACH	5
	HEAT STRAIGHTENING	LUMP SUM	1
	CLEAN EXPANSION JOINTS	EACH	2
**	PROTECTIVE COATING-CONCRETE BENTS AND PIERS (EPOXY)	LUMP SUM	1
	FURNISHING 1 TON ROCK BLANKET	SQ. YD.	2,750
	PLACING 1 TON ROCK BLANKET	SQ. YD.	2,750
	STREETLIGHT REPAIRS	LUMP SUM	1
	LED LUMINAIRE REPLACEMENT	LUMP SUM	1
	TRAFFIC BARRIER REMOVAL	LUMP SUM	1
	STREET CUT RESTORATION	SQ. YD.	15
	GRADING & SITE PREPARATION	LUMP SUM	1
	TRAFFIC CONTROL	LUMP SUM	1
	REMOVE SLIDE DEBRIS AND HAUL OFFSITE	CU. YD.	50
	SAFETY BARRIER CURB	LIN. FT.	200

* INCLUDES WEIGHT OF REPLACEMENT BENT PLATE DIAPHRAGMS AND INTERMEDIATE STIFFENERS. ** ESTIMATED QUANTITY OF 575 SQ. FT. OF PROTECTIVE COATING-CONCRETE BENTS AND PIERS (EPOXY).

ALTERNATE 1 QUANTITIES		
ITEM	UNITS	QUANTITY
PEDESTRIAN FENCE (STRUCTURES)	LIN. FT	1,262

	ALTERNATE 2 QUANTITIES		
	ITEM	UNITS	QUANTITY
***	SECURITY FENCE	LUMP SUM	1

*** ESTIMATED QUANTITY OF 1264 LIN . FT. OF SECURITY FENCE.

	ALTERNATE 3 QUANTITIES		
	ITEM	UNITS	QUANTITY
****	SECURITY FENCE	LUMP SUM	1
	GALVANIZED CORRUGATED METAL SHEET PILING	SQ. FT.	7,560

**** ESTIMATED QUANTITY OF 632 LIN . FT. OF SECURITY FENCE.

ALTERNATE 4 QUANTITIES	_	-
ITEM	UNITS	QUANTITY
INSTALL SHOTCRETE	SQ. FT.	4,750
INSTALL ROCK DOWELS	EACH	190

GENERAL NOTES & QUANTITIES

CENTRAL CONTRAL CONTRA							
F BEA DIS	DATE 2/28/19 DATE PREPARED 02/22/19 ROUTE STATE BEARDSLEY MO DISTRICT SHEET NO. KC 3 COUNTY JACKSON KCMO PROJECT NO. 89005585 BRIDGE NO.						
DESCRIPTION							
DATE							
	BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE & LANDSLIDE KANSAS CITY, MISSOURI						
Dence Schwart Sulte 220 Haw. 3rd Street, SUITE 220 KANSAS CITY, MD 64105 B16/221-4222, FAX 913/441-1468 CERTIFICATE OF AUTHORITY NUMBER F00970024							
	DRAWN BY: JSB Checked by: JMR	_					



3/1/2019

<u>BEAM SUPPORT</u>

TEMPORARY SUPPORT SYSTEM SHALL BE DESIGNED BY THE CONTRACTOR AND SUBMITTED TO THE ENGINEER FOR APPROVAL 4 WEEKS PRIOR TO BEGINNING WORK.

ALL EXISTING BEAMS IN THE SPAN BEING SUPPORTED SHALL BE RAISED SIMULTANEOUSLY 1" ABOVE EXISTING BEARINGS AND SUPPORTED DURING CONCRETE SUBSTRUCTURE REPAIR AND BEARING REPLACEMENT AT BENT NO. 2.

THE TEMPORARY SUPPORTS MUST BE CAPABLE OF SAFELY SUPPORTING 50 TONS PER BEAM (FACTOR OF SAFETY NOT INCLUDED). SEE SPECIAL PROVISIONS.

NO LIVE LOAD OR CONSTRUCTION LOADS SHALL BE ALLOWED ON SPANS 1 OR 2 WHILE ON TEMPORARY SUPPORTS.

FIELD WELDED FILLET WELDS SHALL BE NDT BY THE MAGNETIC PARTICLE PROCESS AS REQUIRED BY AASHTO/AWS D1.5 2002, BRIDGE WELDING CODE CLAUSE 6.7.2.

PAYMENT FOR THE TEMPORARY SHORING SYSTEM SHALL BE SUBSIDIARY TO "TYPE N PTFE BEARINGS", EACH.

MATERIAL AND LABOR REQUIRED IN THE INSTALLATION OF THE INTERMEDIATE BEARING STIFFENERS SHALL BE CONSIDERED TO BE COMPLETELY COVERED BY THE CONTRACT UNIT PRICE FOR FABRICATED STRUCTURAL LOW ALLOY STEEL (MISC.) A709 GR. 50W.



NOTES:

FABRICATED STRUCTURAL STEEL FOR STIFFENERS SHALL BE ASTM A709 GRADE 50W.

CONTRACTOR) —

Detailed FEB 2019 Checked FEB 2019





TEMPORARY SHORING DETAILS - BENT NO. 2



Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_files\Jbrashears\006_Exist Column Repair.dgn 3:50:03 PM



Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_files\Jbrashears\007_Bearing Device Details.dgn 3:50:05 PM

	CHRISTO HAR HAR HAR HAR HAR HAR HAR HAR HAR HAR	MISSOL PPHER B. KER B. Hazeboz IBER 7032758
	DA 2/28	TE B/19
BE,	DATE PF 02/2 ROUTE ARDSLEY ISTRICT K C	REPARED 2/19 STATE MO SHEET NO. 7
	COU JACk KCMO PRO 8900 BRIDG	NTY SON JECT NO. 5585 E NO.
$\left \right $	S03(DB42
DESCRIPTION		
DATE		
	BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE	& LANDSLIDE KANSAS CITY. MISSOU
	Solution	14 W. 3rd Street, SUITE 220 KANSAS CITY, MO 64105 816/221-4222, FAX 913/441-1468 CERTIFICATE OF AUTHORITY NUMBER F00970024

3/1/2019



3:50:07 PM

-×∞∪

3/1/2019

DRAWN BY:

JSB

CHECKED BY:

JMR

-EXISTING BEARING STIFFENER

THE REPLACEMENT BENT PLATE DIAPHRAGMS AND INTERMEDIATE STIFFENERS SHALL BE PAID BY THE BID ITEM "FABRICATED STRUCTURAL LOW ALLOY STEEL (MISC.) A709 GRADE 50W".

ALL BOLTS SHALL BE 3/4"Ø HIGH Strength bolts Astm A325 (type 3). DO NOT REAM DURING FIELD ERECTION. ACCURATELY ALIGN ALL CONNECTIONS BY DRIVING 13/16"Ø DRIFT PINS IN ALL CORNERS AND IN 1/4 OF THE REMAINING HOLES IN EACH PLATE.

ALL STEEL FOR DIAPHRAGMS SHALL CONFORM TO ASTM GRADE 50W REQUIREMENTS.

Enisterher B. Harles PE-2007032758 and DATE 2/28/19 DATE PREPARED 02/22/19 ROUTE STATE MO BEARDSLEY DISTRICT SHEET NO. КC 8 COUNTY JACKSON KCMO PROJECT NO. 89005585 BRIDGE NO. S030B42 BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE & LANDSLIDE ANSAS CITY, MISSOURI Ļ ANS treet, SUITE 220
, MO 64105
2, FAX 913/441-1468
OF AUTHORITY NUMBER U S Φ С U CITY. CITY. -4222. CATE 0 0 4 W. 3r ANSAS (0 16/221-ERTIFI0

CHRISTOPHER HARKER



BARRIER REPLACEMENT

NOTE: BARRIER CURB REPLACEMENTS TO BE PERFORMED AT MIN. 10'0" SECTIONS



TYPICAL REPLACEMENT SECTION

MINIMUM LAP LENGTH OF 2'-11" FOR #5 HORIZONTAL SAFETY BARRIER CURB BARS.

THE CROSS-SECTIONAL AREA ABOVE THE SLAB FOR THE CURB IS 2.28 SQ. FΤ.







TYPICAL REPAIR SECTION USE EXISTING REBAR.

BARRIER CURB REPAIRS

Sheet No. 9 of 24 Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs

3)	\Work_	_files\	Jbrashear	s\009_	_Safety	Barrier	Curb.dgn	3:50:09	РМ

3/1/201

ALL EXISTING REINFORCEMENT IN THE SAFETY BARRIER CURB FROM THE SLAB SHALL BE CLEANED AND REUSED IN PLACE. ADD ADDITIONAL REINFORCEMENT AS

MEASUREMENT OF SAFETY BARRIER CURB REPAIR AND SAFETY BARRIER CURB REPLACEMENT IS TO THE NEAREST LINEAR FOOT.

REMOVE DAMAGED CONCRETE BEFORE

PERFORMING PATCHWORK.

REQUIRED.

BARRIER CURB REPAIR SHALL BE MCIB "SPECIAL AGGREGATE CONCRETE SA-2" OR AN APPROVED SHOTCRETE.

THE MATERIAL USED FOR THE SAFETY

CONCRETE IN THE SAFETY BARRIER CURB Replacement shall be class b-1.

PAYMENT FOR ALL CONCRETE, COMPLETE IN PLACE, WILL BE CONSIDERED COMPLETELY COVERED BY THE CONTRACT UNIT PRICE FOR "SAFETY BARRIER CURB" PER LINEAR FOOT.

BARRIER CURB.

ALL EXPOSED EDGES OF REPAIRED SAFETY BARRIER CURB SHALL MATCH EXISTING

RADIUS OR A 3/8-INCH BEVEL, UNLESS OTHERWISE NOTED.

CURB SHALL HAVE EITHER A 1/2-INCH

TOP OF SAFETY BARRIER CURB SHALL BE BUILT PARALLEL TO GRADE WITH BARRIER CURB JOINTS NORMAL TO GRADE. ALL EXPOSED EDGES OF SAFETY BARRIER

NOTES:

CHRISTOPHER B. HARKER HARKER NUMBER PE-2007032758	ALL				
DATE	7				
2/28/19 DATE PREPARED					
ROUTE STA BEARDSLEY M(
KC 9	NU.				
JACKSUN KCMO PROJECT N 89005585	0.				
BRIDGE NO. SO30B42					
DESCRIPTION					
DATE					
BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE & LANDSLIDE KANSAS CITY, MISSD					
Dence Schwart Control of Control of Control of Control of Control of Control of Certificate OF Authority NUMBER F00970024					
DRAWN BY: JSB CHECKFD BY:					



3:50:11 PM



TRAFFIC CONTROL SUMMARY OF QUANTITIES

	SIGN TYPE	SIZE (SF)	UNIT	TOTAL NEEDED
	MA-84 (24",18") END DETOUR	3	FΔ	1
	$M4 = OR (30" \times 24") DETOUR (PICHT ARROW)$	5	ΓΔ.	10
	$M4 = 9R (30 \times 24") DETOUR (RIGHT ARROW)$	5	ΓΔ.	10
	$M4 = 92 (30^{\circ} \times 24^{\circ}) DETOUR (ELTERATION)$	5	<u>ΕΛ.</u>	8
	$M4 = 93 (30 \times 24) DETOUR (STRAIGHT ARROW)$	5	ΕΔ.	3
	$M4 = 91A (30^{\circ} \times 24^{\circ}) DETOUR (ADVANCE LEFT ARROW)$	5	FA	5
	M4 - 9LD (30"×24") DETOUR (SOFT LEFT ARROW)	5	FA	2
	$M4 - 9RD (30" \times 24") DETOUR (SOFT RIGHT ARROW)$	5	FA	2
	$M4 - 9IDA (30" \times 24") DETOUR (SOFT LEFT ADVANCE ARROW)$	5	FA	1
P11-2	$M4 - 9RDA (30" \times 24") DETOUR (SOFT RIGHT ADVANCE ARROW)$	5	FA	1
48" × 30"	M4-10R (48"x18") RIGHT ARROW WITH DETOUR	6	FA	1
	R_{11-2} (48"x30") ROAD CLOSED	10	FA	2
	R11 = 4 (60"×30") ROAD CLOSED TO THRU TRAFFIC	125	ΕΛ. FΔ	2
	W20-2 (36"×36") DETOUR AHEAD	9	 ΕΔ	2
	$W_{20-3} (36" \times 36") POAD CLOSED AHEAD$	9	ΕΛ. FΔ	2
	SPECIAL 1 (36"x12") REARDSLEY RD	3	ΕΛ. ΕΔ	45
	TYPE III MOVARI E RAPPICADE	5	ΕΛ. ΕΔ	14
	ITPE III MOVABLE BARRICADE		LA.	14
M4-9R 30" x 24" M4-9LA 30" x 24"	RECAPITULATION OF TRAFFIC CONTROL BID I	TEMS		
	ITEM DESCRIPTION	TOTAL	UNIT	
	TRAFFIC CONTROL	1	L.S.	
DETOUR N4-9RDA 30" x 24"	TYPICAL ROAD CLOSURE DETAILS			
Sley Rd	R11-2 48"x30" W20-3 36"x36" GUONE HIL CLOSE CLOS	* THE R1 BE ACC APPROF SIGNIN(ROUTE	4 30" COMPANIED PRIATE DET SHOWN C PLANS	SHOULD WITH THE OUR N DETOUR
<u>1 2.8 2.8 1.1 2.7 4.7 2.8 2.5 3.0</u> TYPE III BARRICADES/	BARRICADES	 	LEGEN	ID BARRICADE



DATE 2/28/19 DATE PREPARED 02/22/19 ROUTE STATE BEARDSLEY MO DISTRICT SHEET NO. KCMO PROJECT NO. 89005585 BRIDGE NO. S030B42 UNITAL SOUNTY S030B42 UNITAL SOUNTY S040	1000 1000 1000 1000 1000 1000 1000 100	PRO SOLO	DF MAS DF MAS DEAT NEWSOI UMEER 006000 -285- 285- 285- 285- 285- 285- 285- 285	P 19 NGIN		· · · · · · · · · · · · · · · · · · ·	_				
O2/22/19 ROUTE STATE BEARDSLEY MO DISTRICT SHEET NO. KC 11 COUNTY JACKSON KCMO PROJECT NO. 89005585 BRIDGE NO. S030B42 NOILLING S030B42 VANSS CITV. MISSONKI KANDSLIDE NO. S030B42 VANSS CITV. MISSONKI KANSS CITV. MISSONKI KAN	DATE 2/28/19 DATE PREPARED										
BEARDSLEY MO DISTRICT SHEET NO. KC 11 COUNTY JACKSON KCMO PROJECT NO. 890055885 BRIDGE NO. S030B42 VILLE DAWAGE % LANDSLIDE % LANDSLIDE % LANDSLIDE KANSAS CITY. MISSOURI	ROUTE STATE										
COUNTY JACKSON KCMO PROJECT NO. 89005585 BRIDGE NO. S030B42 S030B42 S018 FIKE DAMAGE & LANDSLIDE KANSAS CITY, MISSOURI	BEARDSLEYMODISTRICTSHEET NO.KC11										
BEIDGE NO. SO30B42 BRIDGE NO. SO30B42 BRIDGE REPAIRS 2018 FIRE DAMAGE & LANDSLIDE KANSAS CITY, MISSOURI											
BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE & LANDSLIDE KANSAS CITY, MISSOURI		ксмо I 89(BR	PROJ DO5 IDGE	55 55	85 0.	10. 5					
Date Description BEARDSLEY ROAD BRIDGE REPAIRS Description Co18 FIRE DAMAGE Landslide & Landslide Landslide KANSAS CITY, MISSOURI Landslide		S0	30	B	42						
BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE & LANDSLIDE & LANDSLIDE KANSAS CITY, MISSOURI	DESCRIPTION										
BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE & LANDSLIDE KANSAS CITY, MISSOURI	DATE										
-		BEARDSLEY ROA BRIDGE REPAIR	2018 FIRE DAMA	& LANDSLIDE	KANSAS CITY, MISS						
		DR	AWN JSI	B` B	ŕ:						
DRAWN BY: JSB		CHF	CKE	DE	3Y:						

3/1/2019



Detailed FEB 2019 Checked FEB 2019 GENERAL NOTES – All work shall conform to the latest APWA Standard Specifications and Design Criteria, Division II, and Kansas City, Missouri Supplements, Standards and Utility Cut regulations. Excavations shall be protected at all times. Once excavation is made, work shall continue on a workday basis until final restoration is complete. Cuts in roadways shall be plated or temporarily filled and capped with cold mix asphalt when work is not being performed. Trees shall be protected from damage both above and below ground. City Forester at 513–9550 must be contacted when digging within five (5) feet of a tree or when any damage to the tree or a root over three (3) inches occures.

 EXCAVATIONS — The top dimension of the excavation shall be equal to or greater than the bottom dimension. (All sides of the excavation shall be vertical or lay back greater than vertical before beginning backfill.)

BELL HOLE EXCAVATIONS — Excavation around underground facilities wider than surface opening will be allowed if the excavation is backfilled within 24 hours with flowable backfill as stated in 3 below. If unable to complete in the time frame, then the unsupported subgrade and pavement shall be removed to meet the provisions of section 1 above.

- 2. BEDDING Utility bedding shall be granular bedding meeting 2602, compacted embankment meeting 2602, or flowable fill meeting 2602 unless approved by City. Bedding may extend no greater than 12" above utility. In the downtown loop granular bedding shall not be used.
- 3. BACKFILL Backfill shall not be placed in water or mud. Clean graded rock or frozen material shall not be used as backfill. Backfill material and placement shall meet the requirements of 2602.3. Franchise utilities with an approved compaction testing program may perfrom their own compaction test. all other requirements of 2602.3.C must be met.
- 4. ROADWAY SURFACES Surfacing shall be of same type of materials as the existing surface. The finished surface shall be flush with the surrounding surface and shall match the slope and contours of the surrounding pavement.
 - A. Portland Cement Concrete (Detail 4)

If the street cut is in a concrete street, the patch shall extend to the nearest joint in all directions. The patch shall be saw cut and all load transfer devices, expansion joints and reinforcing steel placed prior to placing the new concrete. Concrete shall be placed to the current thickness of pavement or ten (10) inches, whichever is thicker. The concrete must match the color and pattern of the previous pavement.

B. Asphalt - (DETAIL 1)

Pavement shall be removed twelve (12) inches beyond the edge of the disturbed subgrade or pavement, whichever is greater. If the excavation is within three (3) feet of an existing joint or cut, @ lane line or roadway edge the surface shall be extended to that point. Tack coat shall be applied (Section 2204), surface placed and compacted (Section 2205.3) and joints sealed (Section 2206.2). If asphalt is not available at the time repairs are made, concrete may be brought to the surface as a temporary repair. Once asphalt is available, the top 2" of the concrete shall milled out and 2" of asphalt put back.

- C. Other Materials
 - Brick and other pave replaced with matchin
 (8) inch concrete bas
 - Oiled crushed rock r
 of Type 3 asphaltic
 six (6) inches of unit
- Earth or crushed roo twelve (12) inches of
- All others shall be r
- 5. OTHER SURFACES (Backfill und details for p
 - A. Sidewalks, Curbs and Drib be removed to the neare Restoration shall match t pattern and shall comply
 - B. Grass Areas Finish to compacted to 90%. Seec as appropriate.
 - C. All Other Areas Replace
- 6. MISCELLANEOUS REGULATIONS
 - A. Permits are required before must be on site during w
 - 1. Excavation Permits:
 - 2. Traffic Control Perm
 - B. Notifications required bef
 - 1. 2 Working Day Mini
 - 2. 24–Hour Minimum:
 - C. Permit holder must have be void. Contact utility of fax 513-4717, to request
 - D. Repairs shall match existi
 - E. Any Pavement Markings re replaced with like materic



Sheet No. 12 of 24

			−−−−−−−−−−−−−−−−−−−−−−−−−−−−−−−−−−−−	A GOLDENSON	CF M CF M	THE TE	
er type materials :	shall be			2	/28	3/1	9
ng materials place	ed over eight			о, О	ate pf 2/2	repare 2/1	:D 9
se similar to DETA coads shall have f	AL 1. (4) inches			ROUT	E	S	
concrete placed ov	ver a minimum of		D: BF4	ISTRI	ICT	SHE	UU Et No.
treated compacted	aggregate base.			KC	>		12
f untreated compa	icted aggregate.			J	ACK	s di	N
eplaced as directe	d by the City.			ксма	D PRO	JECT	NO.
er all surfaces sh	all be as shown in			<u>Е</u>	BRIDG	E NO	
avement.)				S	030		2
veways — Any sec st joint (Section 2 he existing surfac with the appropri	tion that is cut shal 209.3A and 2301.3A e material and joint ate standards.	l).					
grade with six (6) d or sod (Section) inch topsoil 2400) area		IPTION				
e as directed by f	the City.		DESCR				
ore working in rig vork.	ht—of—way, which						
Public Works 513 Park Dept. (513— nit: 513—2670	-2670 7606)		DATE				
ore actual excavat	ion begins:	7			1.1		
Public Works 513-	-4701.	5.		ROAD	AIRS	IDE MISSO	
inspection of bac cut inspection sect t inspection in adv			RDSLEY	DGE REF FIRE D	LANDSL	•	
ing street slope a	nd grade.			BEA	BRI 2018	ANC &	
emoved by the re	pairs must be					¥	<u> </u>
als.							
or of Dublic Works	Data						68 BER F00970024
	Dale					20	-14 NUM
Entry No.					11	Z ⊤	/441 ⊤Y
Kansas Cil Public Works Engineerir	y, Missouri Department ng Division					+, SUIT	64105 4X 913/ 4UTHORI
					IJ	Г 0 0	°, ∩ 0 F 0 F
UT					C	1 S +	174 • 1222
ION	SR-1					310	
	(PG 1 of 3)					≥	NSAS SAS SAS SAS
wn dy J.A.N.	revisea Mar. 201/						KA CEF
					DRAWN	N BY:	
				С	HECKE	ED BY	′ •



Sheet No. 13 of 24

				DATE PF	TE B/19	
				02/2	2/1	9
			F		SI	
ns 18 incres in ai na. bv reinstalling	ameter or less the oriainal		DI	RDSLET	SHEE	IU T NO.
ntact and installed	with an approved			КC	1	3
nave all cut lines	completely tilled				NTY	J
			K	CMO PRC	JECT	NO.
TWO YEARS OF CO	NSTRUCTION			8900	558	5
)B42	2
2—year schedule o s that may require a non—emergency ed or resurfaced, t	of street making purpose, the		Z			
faced area chall b	o ao followou		1 I C			
acea area snall de	e as tollows:		КIР			
width of the affec	ted lane.)ESC			
the affected lane ever is greater.	or the length					
rface course shall	th of 2 inches be placed.					
nes affected by th above.	ne cut shall be		DATE			
replaced to the e	xisting joints.				١۶	
cuts are separated all be resurfaced w is shown in Detail A MANHOLE: If pa ar opening of 30 d grade of the sur laced with an adju be adjustable to ma and shall be able to and shall be able to 3/4 inches. traffic. Any casting by the Director of quirements do not	by less than the with a single, 3. avement is inches or rrounding stable manhole eet the slope and to be raised and g with a diameter Public Works apply to valve			BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE	& LANDSLIDE KANSAS CITY. MISSD	
or of Public Works Entry No. Kansas Cit Public Works Engineerin	Date y, Missouri Department g Division STANDARD DRAWING NUMBER SR-1 (PG 2 of 3) Revised Mar. 2017	6		benesch	14 W. 3rd Street, SUITE 220	CERTIFICATE OF AUTHORITY NUMBER F00970024
				- ** .		
				DRAWI J	N BY: SB	
				CHECK	ED BY	:

εV.





Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_file



JSB

CHECKED BY:

JMR

3/1/2019

3:51:43 PM



Sheet No. 16 of 24

Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_files\Jbrashears\016_Ped_Fence_Details_East.dgn

	CF 10 CF 10										
	DATE 2/28/10										
	Z/28/19 DATE PREPARED										
	02/22/19 ROUTE STATE										
BE	BEARDSLEYMODISTRICTSHEET NO.										
	KC 16										
	KCMO PROJECT NO. 89005585										
	BRIDGE NO. SO30B42										
DESCRIPTION											
DATE											
	BEARDSLEY ROAD BRIDGE REPAIRS 2018 FIRE DAMAGE	& LANDSLIDE KANSAS CITY, MISSO									
	Solution	14 W. 3rd Street, SUITE 220 Kansas city, Mo 64105 816/221-4222, Fax 913/441-1468 certificate of Authority number F00970024									
		N BY: SB									
		, • MR									

3:51:47 PM





Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_files\Jbrashears\018_Alt 2_Security Fence Plan_Elev.dgn 3:51:52 PM

3/1/2019





Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_files\Jbrashears\020_Alt 3_Security Fence Plan_Elev.dgn

3:51:58 PM 3/1/2019

Y:\Bonner\130500S\00130592.00_Beardsely_Rd_Bridge\Eng_Docs\Work_files\Jbrashears\021_Alt 3_RipRap Location Details.dgn 3:52:07 PM

3/1/2019

STATE

MO

SHEET NO.

23

Ц

NS

et. SUITE 220 D 64105 - AX 913/441-1468 AUTHORITY NUMBER

00⊥ ОФ

d S+r 1 T ≺ • 4 2 2 2 •

LOIC

4 W. ANSAS 16/22

–×∞ບ

3/1/2019

3:52:12 PM

~ H

٠Ē

3/1/2019

Existing ground/rock line.
 Excavation line for girders.
 Excavation line for bent caps.

Note: See "Rock Excavation Bents 8 & 9" sheet for typical cross section through excavation at bent caps.

ž

 \sim

UBSTRUCTURE QUANTITY	TABLE FOR	BENT 2
ITEM		QUANTITY
rilled Shafts (4'-6" diameter)	Lin. Ff.	23.0
ook Sockets (4'-0" diameter)	Lin. F+.	9.2
lass B Concrete (Substr.)	Cu. Yds.	31.0
sinforcing Steel (Bridges) **	Lbs.	8,880
		1

27:01

STATE	PAGJ. NÓ.	SHEET NO.
MD,	-	

· · · · ·				
TAB	LE OF A	NCHOR	BOLT WE	LLS
BENT NO.	″a″ HOLE DIAMETER	"D" SPIRAL DEPTH	"c" HOLE DEPTH	₩5-₩
2	2″	15″	18″	₩5-₩1
3	2″	15″	18″	W5-W1
4	$2\frac{1}{2}''$	2 18" 21"		W5-W2
5	$2\frac{1}{2}''$	18″	21 "	W5-W2
6	3"	25″	28"	W5-W3
7	$2\frac{1}{2}''$	18″	21″	W5-W2
8	$2\frac{1}{2}''$	18″	21″	W5-W2
9	2″	15″	18″	W5-W1

.

	STATE	PADJ. NG.	SHEET ND.
i	HO.	-	

Σ

n

۹.

STATE	PROJ. NO.	SHEET NO.
MO.	-	

The expansion device shall be fabricated and installed

in accordance with the recommendations of the manufacturer, and as set forth in the Special Provisions.

ENGINEERING DIVISION

SHEET 86 DF 103

The contractor must verify all dimensions prior to

All welds shall conform to Section 712 of the Missouri

ą ₹¥:s 2005

AM 4/20.

Г				i		E	BILL	OF RE	INFO	RCIN	G S1	TEEL						Π		·					BILL	OF RE	EINF	ORC I	NG	STE	EL
Ţ,		Mark No;		0. E)	<u>8</u> 8	ΞĘ				Dimensi	ons				t pu t	ath d	Weigh	ن ا ـ	M	kark No		(E)	(S)	Ξł	5		. <u>.</u>	Dimer	is i ons	+	
a a	79	L H	Location •	oxy hape N	bstr.	40. Eac	B	С	D	E		F	Н	K	Nomi Len	Len Len		- Be	ize	ar ¥	Location	shape N	hirrup Ibstr.	01-10S	B	C	D		E	F	
ž	0	ž		e e	53:	5	FT. IN	FT. IN	. FT. IN	I.FT. I	N. FT.	IN.	FT. IN	FT. IN	. FT. 1	N. FT. I	N. LBS.	_ 2	N	2		E C	5 Su		FT. I	4. FT. IN	FT.	3N. FT.	IN.	FT.	IN.
<u> </u>		110	I Soll Potention Big	w []20]				<u>EN</u>	ID BEN	T 1		<u> </u>			T_4	34	3 159			1 3H1	Cap	20	Г Гх	TT	41	3	BENT	3	<u> </u>		
2	<u>, , ,</u>	4 10		ik 20			4												0 5	3H2	Cap	20	x		41	3	-				
2	2 6	6 1F	1 Fillet	E 15	×		0 1	414 1	501	40 9.6	75 0	9.875 (9.875	50 9.875	5	10 6	9 205		0 10 4 6	3H3 3H4	Cap Cap	20	X		11	8					
1		9 1H 5 1H	1 Brg. Beam 2 Brg. Beam	E 20	- X - X	+	43 22	2		+	_				43 22	2 43	2 1,46	8 46	ō 4	3P1	Column	16	x		3	6					\rightarrow
1	2	9 1H	3 Brg. Beam	E 18	X	_	43	2			_				45	8 45 6 11	8 1.55	3 41	1 6	301	Cap	13	s x		4	03	8 4	0 3			
1	2 4	4 18	5 Bookwall	E 20	X	-	22	5	· · ·						22	5 22	5 180	12	2 6	3U2	Cap	10	S X			3	8 4	0			
_	2 6	6 1H 4 1H	6 Backwall 7 Paving Notch	E 20 E 20	X		43 37	6				-			43 37	2 43 6 37	2 130 6 25	14	4 6	3U3	Cap	10	S X			0 1	24	0			
4		5 1H 4 1H	8 Wing 9 Soil Retention Blo	E 20	X	-	6 40	6							6 40	8 6 6 40	8 401 6 216		8 C	3V3	Column	17	x		30	2					-
						-									10	11 10	11 379			3 11 1	Cap		Y	H	0 1	150 9.12	5				
5	2 4	9 11		- 16			3	b				-							, ,,,	311)			-^								
4	5 5 2 5	5 1U 5 1U	1 Brg. Beam 2 Brg. Beam	E 13	s x s x	+	4	3 5.5	5 4 5 4	035	5.5			.	15	10 15	6 695 9 135	-11-													
2		4 1U 5 1U	3 Brg. Beam 4 Brg. Beam	E 10	s x	_		0 10	24	0					5 7	85 87	6 77 5 156										- ·				
3		4 10	5 Paving Notah	E 10	s x			0 14	10	6			·		2	10 2	6 69 0 112								-						
<u>د</u>	, .	* 10	SOFT REFEITFIOL BID			+		4 0											-												
2) 10 3 5) 1V 5 1V	1 Column 2 Backwall	E 20	X X	+	31 5	6							5	1 33 6 5	1 2,84 6 505														
2) 10	2 1V 5 1V	3 Column 4 Wing	17 F 20	X	V 4	34 6	8							36 6	1 36	1 3,10	5													
			Incr.=0.182"			-	6	9						·····	6	96	9 481			• • •	L				•	•	BENT	4			
1) We	5 1W	1 Brg. Beam	E 22	x.	_	0 1	50 9.12	<u>.</u>						23	0 23	0 38	10	0 10	4H1	Cap	20	x		41	3					
_	+			+++		-												10	0 5 0 10	4H2 4H3	Cap Cap	20	X		41	3					_
					11					1						_	_		4 6	4H4	Cap	20	X		11	8					
											_				L.,			50	3 4	4P1	Column	16	X		3	6					
		_			.				BENT	2		,·		·				41	1 6	4U1	Cap	13	s x		4	03	8 4	03			\downarrow
10) 10) 2H 5 2H	1 Cap 2 Cap	20	X		41	3							41	3 41 3 41	3 1.77	21	2 6	402	Cap	10	S X S X			0 1	84	0			
1	10) 2H	3 Cap	18	X		41	3					·		44	1 44	1 1.69 8 70	7 14	46	404	Cap	10	S X			0 2	2 4	0			-
		2								+					-		44 204	40) 8	4V4	Column	17	x	. .	31	4					\square
- 40		1 2P	1 Column	16	- <u>×</u>		3	5 							10		11 291	10) W5	4W2	Сар	22	x		0 1	18 0 9.12	5				
4	6	5 2U	1 Cap 2 Cap	13	s x s x		4 . (23 E	3 4	03	8				16 11	8 16	2 996 1 200			· ·				$\left \right $				<u> </u>		, <u> </u>	-+
Ö 2	4	20	3 Cap	10	s x			0 10	14	0					5	8 5	6 77		_												
14 C	6	5 20	4 Cap		S X	-		0 22							ľ																
₽ <u>40</u>	8	1 21	2 Column	17	X	_	26	3							27	7 27	7 2,94	§				·			}		-				
P 10	W5	i 2W	1 Cap	22	x		0 1	50 9.125	j						23	0 23	0 36		_								<u> </u>				
	+-		\																												
dge.	-	_	· · · · · · · · · · · · · · · · · · ·	+++						-		 -		. 			-		-												
2005 s:*beardstey rd#bri	_6d_1	Detailing		Hook Detoiling A or 6	- - - -			STIR 97 Bor Size #4 #5 #5 #6 Note: Uni "0" is th	RUP HOOK -ades 40 - D Hook 2" 41 2#" 6 4½" 12 ses other will Formation	DIMENS 50 - 60 KS 138' 4 Hook 138' 4 Aor c 4 4' 1 5 ±'' 8 8' se noted. gill bends	IONS 51 • Hook Approx. 3 ³ 3 ³ / ₄ " 3 ³ / ₄ " 4 ¹ / ₂ " diamete and hoo		Detai	oiiina Dimen 90° o ijina Dimensi	alon on		Bar Siz 43 44 45 46 46 46 46 46 46 46 46 46 46 46 46 46	END H B D 2+1** 3** 3-1** 	00K C 18 A or 5" 6" 7" 8" 10' 11' 15"	DIMEN AII C 10° Hook ° 3 ° 4 * 5 ° 4 * 5 ° 4 * 5 ° 4 * 5 ° 7 * 8 * 11	N SIONS W Brades w Sr def S S S S Now S S S S S S S S S S S S S	otes: 1! star ith the ooks ar hown or = stir = bar hown or o. Ea. ominal ending ctual ing	idar sat id bi ith is ith is ith ien dia engi ind	d ha me p ends cate is l ens is l gths f h.	boks and procedure shall b shaet. ad reinfo uded in ons vary ine and ar of bar s are bas as and ar are meas	bends of a as for be in accordent substruct in equation the following sed on out the listed sured alo	ture qu l incre wing i i lengt t to cu for fa ng cent	n 180 d ee star with 1 ments t ine h t dimer bricat(erline	jegree idard the pr ss setwee isions bar .	en din s show se (ne to the	be t ,, ires nens vn 1: e
/20/2		9	90" Stirrup .	135	o• \$`	tirr	υp	on a bar	e some for	uli Dends	und hoo	n Ş	^고 180° 4d	or2∳″min.			#9 #10 #11	10 ³ "	15 ⁴ 17 ⁴ 19 ⁴	11 13 14	4 19" P 14" 22" P 14" 2'~0" R	einford	nts a bing	are ste	based or el (Grad	n actual 19 60) FY	lengths = 60 k	si	Dees	150	ij

AN DETAILED BK CHECKED JCT

05:54

ö

Ŕ

and the

Reinforcing steel (Grade 60) FY = 60 ksi

END HOOK DIMENSIONS										
-		A	sec							
BOP Size	Ð	180*	90* Hook							
5,10		A or C	J	A or G						
å	2 1 "	5″	3"	6″						
8 44	3″	6″	4*	6″						
#5	34"	7"	5″	10*						
希	41/	8″	64	12"						
#1	5 † ″	10"	7"	14″						
#8	6"	11"	8″	16″						
#9	9₽″	15″	11 👬	19*						
#10	10}"	17"	13 🕇 "	22″						
#11	12"	19″	14 7"	2'~0"						
#14	18‡"	2'-3"	217"	2'-7"						

₽ 1

g

14 d.

Φ

5

ardsley s:#De 4/20/2005 ΜM

48

02

÷

---- -- ----

CITY OF KANSAS CITY, MISSOURI BEARDSLEY ROAD SLOPE REPAIRS PROJECT NO. 89008538

Emergency Utility		
UTILITY COMPANY / AGENCY	Contact in Case of Emergency:	Email Address
AT&T	816-275-2721	<u>cp0772@att.com</u>
CenturyLink (Level 3/Quest)	913-645-5032	Jerry.Woodall@level3.com
CenturyLink	800-283-4237	brian.cornish@centurylink.com
Charter (Time Warner Cable)	866-967-7611	<u>steven.baxter@charter.com</u>
Comcast	866-641-1625	derek haber@cable.comcast.com
Consolidated	800-283-4237	OSP kc@consolidated.com
Consolidated	913-322-9953	tim.laforce@consolidated.com
Google Fiber NOC	866-954-1571 877-454-6959	kc-google-uc@google.com
KC Fiber / Link City	816-564-9994	bbrown@kcfiber.com
KCMO Parks & Recreation	311	David.Panek@kcmo.org
KCMO PW - KCMO Fiber System	311	Chris.lockey@kcmo.org
KCMO PW Street Resurfacing	816-513-9871	Corey.goodloe@kcmo.org
KCMO PW Traffic Engineering	816-513-9871	wei.sun@kcmo.org
KCMO PW Street Lighting	816-513-9871	Mahmoud.hadjian@kcmo.org
KCMO PW Neighborhoods	816-513-9871	kerry.kanatzar@kcmo.org
KCMO Water Services,	311 or 513-0209	antice muching the second second
Overflow Control Program	after hours	sstuempfig@burnsmcd.com
KCMO Water Services, Sanitary Sewers	311 or 513-0209 after hours	Karine.papikian@kcmo.org
KCMO Water Services, Storm Water	311 or 513-0209 after hours	Robert.davis@kcmo.org
	311 or 513-0209	Kirk.Rome@kcmo.org;
KCMO Water Services, Water	after hours	Daniel.Sullivan@kcmo.org
KCP&L	816-701-7800	andrew.alexander@kcpl.com
Magellan Midstream	800-720-2417	Tonya.Cape@magellanlp.com
North K.C. School Distr.	816-413-5075	eric.sipes@nkcschools.org
Southern Star Central	913-422-6321	gary.tolle@sscgp.com
Spire Energy (MGE)	314-776-9517	jose.arellano@spireenergy.com
Sprint	913-488-8489	jason.cantrell@sprint.com
Unite Private Network	866-963-4237	sean.brown@upnfiber.com
Veolia Energy (Trigen)	816-889-4977	richard.behrens2@veolia.com
Verizon Communications Inc.	800-624-9675	lester.rutherford@verizon.com
Zayo	816-591-0282	dwight.davis@zayo.com

VICINITY MAP

LOCATION MAP

CITY OF KANSAS CITY, MISSOU BEARDSLEY ROAD SLOPE RE

COVER SHEET

INDEX OF SHEETS:

1.

2. 3.

4.

5.

6.

7.

8.

9.

10.

11.

COVER SHEET U.S.G.S. MAP PLAN VIEW AERIAL IMAGE PLAN VIEW AND UTILITY LOCATIONS GEOLOGIC MAP BEFORE LANDSLIDE CLEANUP TP# 444939 (0 FEET TO 105 FEET) GEOLOGIC MAP BEFORE LANDSLIDE CLEANUP TP# 444939 (105 FEET TO 190 FEET) GEOLOGIC MAP AFTER LANDSLIDE CLEANUP TP# 444939 (0 FEET TO 105 FEET) GEOLOGIC MAP AFTER LANDSLIDE CLEANUP TP# 444939 (105 FEET TO 190 FEET) SLOPE REPAIR DESIGN - ELEVATION VIEW SLOPE REPAIR DESIGN - CROSS SECTION A-A' SITE PHOTOGRAPHS BEFORE LANDSLIDE CLEANUP

RI	Project Number	Date
PAIRS	89008538	FEB. 2019
	Checked by	Drawing No.
	ALP	1

Views.dwg 3:26.21 pm (mik) Rock Bolting\CAD\Plan Sheets\Plan 2019 Road F February 26, : J:\Beardsley F

.0	E OF M	NARA A
84	DARYI A PODLISK	
	PE-201	rlut
ALL	SION	
2	6 Fest	gaan

and the second se		
RI	Project Number	Date
AIRS	89008538	FEB. 2019
	Checked by	Drawing No.
	ALP	2
AIICO	Checked by ALP	Drawing No.

SOURCE: GOOGLE EARTH PRO IMAGE DATED MARCH 2016.

CITY OF KANSAS CITY, MISSOURI BEARDSLEY ROAD SLOPE REPAIRS

AERIAL IMAGE PLAN VIEW AND UTILITY LOCATIONS

1. ALL UTILITY LOCATIONS SHOWN HERE ARE APPROXIMATE BASED ON BEST AVAILABLE INFORMATION AND ARE NOT GUARANTEED AS TO ACCURACY. CONTRACTOR SHALL CONTACT UTILITIES TO VERIFY EXACT LOCATIONS. OTHER UTILITIES BESIDES THOSE SHOWN HERE MAY BE PRESENT; CONTRACTOR SHALL CONTACT MISSOURI ONE-CALL A MINIMUM OF 72 HOURS PRIOR TO BEGINNING WORK.

2. KCP&L DISTRIBUTION LINE POWER POLES WILL NEED TO BE BRACED DURING CONSTRUCTION.

LEGEND:

----- OHE ---

PP 🔴

ДLЬ

30" RCP

_____SI -

NOTES:

ELECTRIC (OVERHEAD)

POWER POLE

STREET LIGHT CONDUIT

LIGHT POLE

STORM SEWER

FIBER OPTIC (OVERHEAD)

2019 3:17.51 pm (mik) Road Rock Bolting\CAD\Plan Sheets\Revised Geologic Profiles.dwg February 26, J:\Beardsley F

1						
		Ц				
		Ш.				
		Ë				
		105				
		АТ				
		ц				
		СH				
$\langle / / / / \rangle$		AT				
		Σ				
$\langle / / / / \rangle$	\square					
				2222-		
			E OF	Mis	2	
$\Lambda / / / / / X$		N.	A CONTRACT	30-	名	
90 10	0	8 ×	A PODI	RYL LSKA	国	
	I		NUM	k Kru	K	
		E.	PE-2016	340092		
		No.	OPIC RUA	ENC		
			27 Par	ange	<i>P</i>	
			10163	• 1 -		
			-			
APROXIMATE	TE		Z	¥		
EPICTED BY WHA	λT		0	5		
MAPPING			SCA	SCALE: 1	=10'	
ואנ EPAIR		Project Ni 89008	umber 5 38	FE	Date E B. 2019	
DE CLEANUP		Checked	by	Dr	awing No.	┥
FEET)		ALF			4	

40 30 HOIHAN 20 30 20 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20	"JEKYL" GRAFFITI	MARK ON WALL			
Image: Section of the section of t		— 40			
Image: Second		— 30	Е НЕІСНТ (FEET)		
I = 10 $I = 10$ $I = 0$ I		— 20	SLOPE		
Image: Second State Sta	- , ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,	— 10			
Image: Night of the second		0 190		A PODUS A PODUS A PODUS A PODUS A PODUS PE-201604 PE-201604 PE-201604 PE-201604 PE-201604 PE-201604 PODUS PE-201604 PODUS PODUS PODUS PODUS PODUS PODUS PE-201604 PODUS PE-201604 PODUS PODUS PODUS PODUS PODUS PODUS PODUS PODUS PE-201604 PODUS PODUS PODUS PE-201604 PODUS PODUS PE-201604 PODUS PE-201604 PODUS PE-201604 PODUS PE-201604 PE-20	MISSOULELA WILL ER 20092
JRIProject NumberDatePAIRS89008538FEB. 2019DE CLEANUPChecked byDrawing No.FEET)ALP5	TE XIMATE WHAT 6			Z 0 SCA	5 10 LE IN FEET SCALE: 1"=10'
DE CLEANUP Checked by Drawing No. FEET) ALP 5	JRI PAIRS			Project Number 89008538	Date FEB. 2019
	DE CLEANI FEET)	UP		Checked by ALP	Drawing No. 5

IRI	Project Number	Date
PAIR	89008538	FEB. 2019
E CLEANUP	Checked by	Drawing No.
EET)	ALP	6

MATCH LINE AT 105 FEET

\bigvee	/	· /	\bigvee			\setminus	1/	V	/	,		\bigvee	//
	\bigvee				\bigvee		/			\ 			\bigvee
		•	0		0]	0		0			
					5'								LS
		0		0		•	0		0		•		
			0		0	o]	0		0			SH
													LS
		0		0		0	•		0		0		SH
			0		0	•		0		0			LS
													SH
													LS
												Δ	
			/				a = <i>i</i> a						
	REPA	IR PROFI	LE (APF	PROXIM	1ATEL	<u>Y 25 FT</u>	OF 19	D FT-W	IDE LA	NDSLI	DE IS SH	<u>OWN)</u>	

Project No, 60522646

ALTERNATE 4 - SLOPE REPAIR DESIGN -

QUANTITIES (ESTIMATED):

~190 ROCK DOWELS

_EGEND:

• ROCK DOWEL

NOTE:

. ROCK DOWEL SPACING OF 5-FEET VERTICAL AND HORIZONTAL IS APPROXIMATE. ADJUSTMENTS TO THE SPACING MAY BE NEEDED DURING CONSTRUCTION TO ACCOUNT FOR SLOPE CONDITIONS, WITH PRIOR ENGINEER'S APPROVAL.

NOT TO SCALE

IRI	Project Number	Date
PAIRS	89008538	FEB. 2019
	Checked by	Drawing No.
ELEVATION VIEW	ALP	8

NOTE: ROCK DOWEL LENGTHS ARE 10 FEET.

CROSS SECTION A-A'

CITY OF KANSAS CITY, MISSOU BEARDSLEY ROAD SLOPE RE

ALTERNATE 4 - SLOPE REPAIR DESIGN - CF

NOT TO SCALE

IRI	Project Number	Date
PAIRS	89008538	FEB. 2019
	Checked by	Drawing No.
ROSS SECTION A-A'	ALP	9

VIEW LOOKING NORTH (NOVEMBER 2016)

VIEW LOOKING EAST (JULY 2016)

VIEW LOOKING SOUTH (NOVEMBER 2016)

2380 McGee Street, Suite 200 Kansas City, Missouri 64108

Project No, 60522646

CITY OF KANSAS CITY, MISSOU BEARDSLEY ROAD SLOPE REP

SITE PHOTOGRAPHS BEFORE LANDSL

RI	Project Number	Date
PAIRS	89008538	FEB. 2019
IDE CLEANUP	Checked by ALP	Drawing No. 10

<u>PHOTO 1</u>

PHOTO 2

PHOTO 4

PHOTO 5

2380 McGee Street, Suite 200 Kansas City, Missouri 64108

Project No, 60522646

AECOM

CITY OF KANSAS CITY, MISSOUR BEARDSLEY ROAD SLOPE REP

SITE PHOTOGRAPHS AFTER LANDSLI

<u>PHOTO 7</u>

dwg. Site Photos. February 26, 2019 3:32.31 pm (mik) J:\Beardsley Road Rock Bolting\CAD\Plan Sheets\Revised

PHOTO 3

PHOTO 6

NOTE: PHOTOS 1-7 ARE ARRANGED FROM NORTH TO SOUTH LOOKING EAST.

RI	Project Number	Date
PAIRS	89008538	FEB. 2019
DE CLEANUP	Checked by ALP	Drawing No. 11